

**PATENT APPLICATION
DOCKET NO. (4988US)**

NOTICE OF EXPRESS MAILING

Express Mail Mailing Label Number: EL 740537471 US
Date of Deposit with USPS: 7/20/01
Person making Deposit: Jured Turner

APPLICATION FOR LETTERS PATENT

for

VEHICLE STORAGE DEVICE

INVENTORS:

Bryon C. Jones
Nola M. Samuels

Attorney:
Devin R. Jensen
Registration No. 44,805
Edgar R. Cataxinos
Registration No. 39,931
TRASKBRITT, P.C.
P.O. Box 2550
Salt Lake City, Utah 84110
(801) 532-1922

VEHICLE STORAGE DEVICE

BACKGROUND OF THE INVENTION

[0001] Field of the Invention: The present invention relates to vehicle storage devices. More particularly, the present invention relates to rear-mounted, removable vehicle storage devices for recreational vehicles, sports-utility vehicles, and the like.

[0002] State of the Art: The use of external storage devices with vehicles provides an excellent way to increase the carrying capacity of the vehicle. For example, numerous storage devices have been invented to carry additional luggage on the roof rack of the vehicle. One such storage device is the Rocketbox made by Yakima. The Rocketbox is a hard plastic or fiberglass storage container that is aerodynamically shaped to cut through the wind. Attached to the roof of a vehicle, the Rocketbox allows the user to store additional luggage or materials outside of the vehicle, thereby freeing up interior space within the vehicle. Other storage devices, similar to the Rocketbox, are made and sold by other companies.

[0003] Similarly, square or rectangular boxes made of plastic are used for storing luggage or other items on the tops of recreational vehicles (RV). The storage device is attached or fixed to the roof of the RV. A ladder found on the back portion of an RV commonly provides access to such storage devices. Use of such storage boxes, however, can be undesirable. First, because the storage box mounts to the roof of the RV, access to the storage box is difficult. To store items within the storage box, a user must carry those items up a ladder or devise some other method of moving the items to be stored to the roof of the RV. Furthermore, the additional height of the storage box on top of the RV can pose clearance problems depending upon the height of the RV to which the storage device is attached.

[0004] Other alternative storage methods have also been disclosed for vehicles. For example, United States Patent No. 4,159,844 to Weiner discloses storage drawers that increase the carrying capacity of an RV by providing large drawers that can be pulled out from below the RV's under frame. Although such storage drawers provide additional storage for the RV, the clearance under the RV can be limited by their use.

[0005] Accordingly, it is desirable to provide a vehicle storage device capable of storing items while at the same time providing easy access to the stored items.

SUMMARY OF THE INVENTION

[0006] The present invention relates to vehicle storage devices, and more particularly, to rear-mounted, removable vehicle storage devices. The vehicle storage devices of the present invention mount to the back of a vehicle, on a ladder, by tire mount, by equalizer hitch mount, or by bumper mount. The vehicle storage devices may also include additional attachments or fixtures for transporting bicycles, skis, snowboards, or other outdoor recreational equipment.

[0007] In one embodiment of the present invention, the vehicle storage device comprises a structural frame covered with a material, forming a storage space within the covered structural frame. Typically, the frame is constructed of materials such as plastic, metal, composites or wood. The material covering the frame may include metal, plastic, fiberglass, cloth, or other material sufficient to protect items stored within the vehicle storage device from the weather or elements. Preferably, the material is durable and water resistant. An access portal in the material covering the frame provides ingress and egress to the interior of the vehicle storage device for inserting or removing items from the vehicle storage device. The access portal may be secured in position with fasteners such as VELCRO, zippers, hooks, snaps, clamps, or door latches, depending upon the type of material used to cover the frame. A removable portion of material covering a top portion of the frame may act as a flap, cover, or lid through which items may also be inserted or removed from the storage space of the vehicle storage device.

[0008] Hooks attached to the back portion of the frame of the vehicle storage device may be used to hang the vehicle storage device on a ladder of a vehicle, such as a recreational vehicle (RV). Additional clamps may be used to help secure the vehicle storage device to a vehicle ladder once the vehicle storage device is attached to the ladder by hooks. The clamps may include locking clamps to help prevent theft of the vehicle storage device.

[0009] In another embodiment of the invention, adjustable or fixed clamps attached to the frame of the vehicle storage device are used to clamp the vehicle storage device to a vehicle ladder.

[0010] In still another embodiment of the present invention, the vehicle storage device includes a mounting plate attached by a hinge to the back portion of the frame. Adjustable and/or fixed clamps attached to the mounting plate may be used to secure the vehicle storage device to a ladder on the back of a vehicle. Once attached, the frame of the vehicle storage

device may be swung away from the mounting plate and ladder through use of the hinged attachment between the frame and mounting plate. Thus, the ladder may be used without removing the vehicle storage device from the ladder. The frame of the vehicle storage device may be secured to the mounting plate by any type of clasp or clamping device known in the art.

[0011] Alternate attachments may also be used to secure the vehicle storage device to the back of a vehicle. Such attachments include equalizer hitch mounts, bumper mounts, tire mounts, and the like. The mounts may attach to the frame of the vehicle storage device, or a mounting plate, thereby securing the vehicle storage device to the back of a vehicle.

[0012] Additional equipment carriers may also be incorporated with the vehicle storage device. A bicycle rack, attached to the frame of the vehicle storage device or to a mounting device, may be used to transport bicycles with the vehicle storage device. The bicycle rack may also include a pivot point allowing the bicycle rack to be rotated away from the vehicle storage device, thereby providing uninhibited access to the vehicle storage device. Similarly, racks for carrying skis, snowboards, or other recreational equipment may also be incorporated with the vehicle storage device.

[0013] Optional wheels may be included with the vehicle storage device. Typically, two wheels mounted or moveably secured to the bottom of the frame of the vehicle storage device facilitate easy transportation of the vehicle storage device when it is disengaged from a vehicle. Tilting the vehicle storage device onto the wheels allows a person to either push or pull the vehicle storage device along a surface.

DESCRIPTION OF THE DRAWINGS

[0014] While the specification concludes with claims particularly pointing out and distinctly claiming that which is regarded as the present invention, the advantages of this invention can be more readily ascertained from the following description of the invention when read in conjunction with the accompanying drawings in which:

[0015] FIG. 1 illustrates a perspective view of one embodiment of the present invention;

[0016] FIG. 2 illustrates a back view of one embodiment of the present invention;

[0017] FIG. 3 illustrates a back view of the frame of the embodiment illustrated in FIGS. 1 and 2;

- [0018] FIG. 4 illustrates one embodiment of the present invention attached to a vehicle ladder;
- [0019] FIG. 5 illustrates an alternative embodiment of the present invention;
- [0020] FIG. 6 illustrates an alternate embodiment of the present invention including a bicycle mount incorporated with the vehicle storage device;
- [0021] FIG. 7 illustrates an alternate embodiment of the present invention including a ski/snowboard mount incorporated with the vehicle storage device; and
- [0022] FIG. 8 illustrates a rear view of one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0023] The present invention relates to vehicle storage devices, and more particularly, to rear-mounted vehicle storage devices and the like. One embodiment of the vehicle storage device 100 of the present invention is illustrated in FIGS. 1 through 4. As illustrated, the vehicle storage device 100 comprises a frame 110 covered by material 120. The material 120 covering the frame 110 forms a storage compartment or space within the vehicle storage device 100. In this particular embodiment, the frame 110 and the material 120 of the vehicle storage device 100 form a rectangular shaped box having a front portion 121, a back portion 122, a right sidewall 123, a left sidewall 124, a top portion 125, and a bottom portion 126. The top portion 125 of the illustrated embodiment is a top cover 128 constructed of material 120. It is understood that the vehicle storage device may take on different shapes depending upon the configuration of the frame 110 and the material 120 covering the frame 110. An access portal 130, integral to the front portion 121 of the vehicle storage device 100, provides access to the interior storage area or space created by the material 120 around frame 110. A mounting plate 150, shown in FIG. 2, connects to frame 110 via a hinge 152 exterior to the back portion 122 of the vehicle storage device 100. The hinge 152 protrudes through material 120 in the back portion 122 of the vehicle storage device 100. Mounting plate 150 also includes two fixed clamps 154 and two movable clamps 156 for attaching the vehicle storage device 100 to a vehicle ladder. Optional wheels 160 and handle 170 may be mounted to frame 110 through material 120 to facilitate mobility of the vehicle storage device 100 when disengaged from a vehicle.

[0024] A cutaway portion of material 120 in FIG. 1 reveals a portion of frame 110 under material 120. A rear view of frame 110 is shown in FIG. 3 without the presence of material 120 covering frame 110. In a preferred embodiment, frame 110 is rectangular shaped

and formed from strong, corrosion-resistant tubing. For example, tubing constructed from materials such as aluminum alloys, galvanized steel, carbon steel, stainless steel, plastic, or polymeric material may be used to form frame 110. Typically, metal tubing members are welded together to form frame 110. Other methods of securing the tubing members together to form frame 110 may also be used, especially when frame 110 is constructed of a plastic or polymeric material. For example, frame 110 may be constructed of detachable portions to allow the frame to be disassembled and more readily stored. Tubing members may clamp, screw or otherwise attach to form frame 110. Also, hinging mechanisms (not shown) may be used to allow frame 110 to fold or collapse for storage. Although the size of frame 110 may vary, it is preferred that frame 110 does not exceed the height or width of the vehicle to which it will be attached. Furthermore, frame 110 may be formed in any preferred shape.

[0025] In addition, frame 110 preferably includes a hinge 152 fixed to at least one support member or tube of frame 110. Hinge 152 may be welded to frame 110 or secured to frame 110 using other methods known in the art. Additionally, hinge 152 may be a detachable hinge that permits the hinge 152 to be disconnected so that the frame 110 of the vehicle storage device 100 may be detached from the mounting plate 150. This allows the mounting plate 150 to be set in position and left in a mounted position while the frame 110 and contents contained in the vehicle storage device 100 are removed.

[0026] An optional base plate 112 may be inserted within frame 110 to provide support to frame 110 or a better surface for supporting items stored within the vehicle storage device 100. Preferably, the optional base plate 112 is constructed of a durable material such as metal or hard plastic and is formed so that it may be inserted and removed from frame 110 as desired. For example, the optional base plate 112 may be configured as a flat panel with cutout corners to rest on the bottom tubing members of frame 110. A person using the vehicle storage device 100 could then insert or remove the optional base plate 112 as desired. Alternatively, optional base plate 112 may be permanently connected to frame 110 by welding, riveting or other substantially permanent connection.

[0027] Material 120 encloses frame 110, forming the storage space of the vehicle storage device 100. Preferably, material 120 is durable and water-resistant to help prevent exposure of the contents stored in the vehicle storage device 100 to the elements. Furthermore, the interior surface of material 120 may be padded or lined to protect the contents stored within

the vehicle storage device 100. For example, material 120 may comprise a fleece-lined, waterproofed vinyl with the fleece-lined portion of material 120 on the interior of the vehicle storage device 100. Alternatively, material 120 may include COVER LITE, neoprene, SUNBRELLA fabric by Glen Raven Custom Fabrics, lacing/ziptie, carbon fiber, steel, fiberglass, aluminum products, or plastic products. Grommet holes (not shown) may also be included in portions of material 120 to allow the attachment of bungee cords, ropes, or bicycle locks to the vehicle storage device 100.

[0028] As illustrated in FIGS. 1 and 2, material 120 covers frame 110 forming front portion 121, back portion 122, right side wall portion 123, left side wall portion 124, and bottom portion 126. Material 120 may be permanently fastened to frame 110 or it may be removable. For instance, material 120 may be configured as a bag having a bottom and four sidewalls such that material 120 may be pulled onto frame 110 and secured thereto to form a vehicle storage device having an open top. Material 120 may be secured using fasteners known in the art such as snaps, hooks, ties, VELCRO, zippers, and the like. This allows material 120 to be removed for storage or for cleaning.

[0029] A removable top cover 128 encloses the top portion 125 of the vehicle storage device 100. Preferably, top cover 128 is made of the same material used to make material 120. Top cover 128 may be secured to either frame 110 or material 120 using fasteners such as buckles, zippers, VELCRO, snaps, hooks, or the like. Alternatively, a back portion of top cover 128 may be securely attached, or integral with, the portion of material 120 forming the back portion 122 of the vehicle storage device 100 such that the top cover 128 is permanently attached to material 120. The top cover 128 may be lifted or placed over the top portion of the vehicle storage device 100 to protect the contents stored therein from the elements.

[0030] An access portal 130 integral with material 120 provides access to the interior of the vehicle storage device 100. Preferably, access portal 130 is integral with the front portion 121 of the vehicle storage device 100. However, access portals 130 may also be located in the right sidewall 123, left sidewall 124 or back portion 122 of the vehicle storage device 100. Multiple access portals 130 are especially useful where the vehicle storage device 100 contains multiple compartments.

[0031] The access portal 130 is typically constructed of the same material as material 120. The access portal 130 is connected to material 120 using fastening devices well known in

the art such as VELCRO, zippers, snaps, ties and the like. For example, FIG. 1 shows a zipper 132 connecting a portion of access portal 130 to material 120. A similar zipper 132 on the opposite side of access portal 130 connects that portion of the access portal 130 to material 120. The top portion of the illustrated access portal 130 may similarly be zippered, or otherwise attached, to material 120. Unzipping both zippers 132 allows access portal 130 to flap downward, revealing the interior of the vehicle storage device 100. In this manner, the storage space within the vehicle storage device 100 may be accessed to place or remove items therein.

[0032] In addition to the fastening device, the access portal 130 or material 120 may include protective flaps to cover the fastening devices and to help prevent exposure to the elements. For instance, material 120 may include an additional flap of material around zippers 132 such that when zippers 132 connect the access portal 130 to material 120, the zippers 132 are covered and protected by the additional flap of material. Such protective measures are commonly used with fastening devices and shall not be explained further herein.

[0033] A mounting plate 150 may be attached to frame 110 through material 120 on the back portion 122 of the vehicle storage device 100. Preferably, mounting plate 150 is attached to frame 110 via hinge 152. The positioning of hinge 152 along one side of mounting plate 150 and frame 110 allows separation of mounting plate 150 and frame 110 on the opposite side of the vehicle storage device 100. In order to prevent frame 110 from swinging on hinge 152 an additional clasp 158, or other fastening device, secures frame 110 and mounting plate 150 opposite hinge 152.

[0034] Attached to mounting plate 150 are fixed clamps 154 and movable clamps 156 used to secure the vehicle storage device 100 to a ladder of an RV or other vehicle. Typically, fixed clamps are welded to mounting plate 150 or are otherwise attached thereto. Moveable clamps 156 are attached to mounting plate 150 through holes in the mounting plate 150 allowing lateral movement of the movable clamps 156. To adjust the movable clamps 156, a standard screw or bolt may be loosened to allow the movable clamp 156 to move along the hole. Once positioned, the movable clamp 156 is secured in place by retightening the screw or bolt. Other known mechanisms or devices may also be used to secure the movable clamps 156 into the desired position. For instance, the movable clamps 156 may be fitted with a quick release device that allows a user to easily disengage the movable clamp 156 from a position on the mounting

plate 150, move the movable clamp 156, and reengage the quick release mechanism to secure the movable clamp 156 to the mounting plate 150.

[0035] Fixed clamps 154 mount to one ladder post securing one side of the back portion 122 of the vehicle storage device 100 to the ladder. The movable clamps 156 are secured to a second ladder post, thereby securing the opposite side of the back portion 122 of the vehicle storage device 100 to the vehicle's ladder. The movable clamps 156 allow the vehicle storage device 100 of the present invention to be fitted to ladders of varying sizes. For larger ladders, the movable clamps 156 may be positioned farther from the fixed clamps 154. Similarly, smaller ladders may require that the movable clamps 156 be positioned closer to the fixed clamps 154 to attach to the ladder. Once attached, the fixed clamps 154 and movable clamps 156 secure the mounting plate 150 to the ladder of a vehicle.

[0036] Both fixed clamps 154 and movable clamps 156 may be any type of clamps capable of securing the vehicle storage device 100 to a ladder and supporting the weight of the items stored therein. Preferably, the fixed clamps 154 and movable clamps 156 include rubber or plastic inserts or padding to prevent damage to a ladder to which the clamps are attached. The clamps may be attached to a ladder post using spring-loaded clamping mechanisms, nut-and-bolt mechanisms, or other forms of clamping attachment known in the art. Fixed clamps 154 and movable clamps 156 may also include locking mechanisms for locking the clamps in a clamped position. Such locking clamps may be used to help prevent theft of a vehicle storage device 100 once clamped to a vehicle.

[0037] The vehicle storage device 100 of the present invention may also include wheels 160 attached to the frame 110, the mounting plate 150, or elsewhere on the vehicle storage device 100. Wheels 160 provide an easy way to move the vehicle storage device when disengaged from a vehicle. A handle built into the vehicle storage device 100 may be used to tip the vehicle storage device 100 onto its wheels 160 so that the vehicle storage device 100 may be pushed or pulled along a surface, such as the ground.

[0038] FIG. 4 depicts a vehicle storage device 100 of the present invention mounted on a vehicle ladder 900, such as the ladder of an RV. As illustrated, the vehicle storage device 100 is disengaged from the clasp 158 such that the storage area defined by frame 110 and material 120 swings freely on hinge 152. This allows an individual to use the vehicle's ladder 900 even if the vehicle storage device 100 is attached thereto. Because the mounting plate 150

does not obstruct the rungs of the ladder 900, a person may swing the storage area of the vehicle storage device away from the ladder 900 during use. Before proceeding, the storage area of the vehicle storage device 100 may be secured to the mounting plate with clasp 158.

[0039] In an alternate embodiment of the present invention, the vehicle storage device is formed of a material such as fiberglass, plastic, injection molded plastic, metal, or the like. Vehicle storage devices 500 constructed from materials such as these provide additional protection from the elements and security of the contents stored in the vehicle storage device 500. They may also provide additional structural support, allowing greater loads to be carried within the vehicle storage device 500. The vehicle storage device 500, illustrated in FIG. 5, has no frame; rather, the structural integrity of the vehicle storage device 500 is maintained by the strength of the material 520 from which it is constructed. For instance, material 520 of vehicle storage device 500 may be steel or DIAMOND PLATE metal. A mounting plate may be mounted on the back portion of the vehicle storage device 500 just as it is mounted on the vehicle storage device illustrated in FIG. 1. However, the mounting plate hinge may be integral, or welded, to the material 520. The mounting plate may also be made of the material 520 used to make the vehicle storage device 500. Alternatively, the mounting plate may be constructed of some other durable material capable of holding and supporting the vehicle storage device 500 and stored contents when swung open.

[0040] Instead of a material flap, the access portal in vehicle storage device 500 may be a door 530 mounted on one or more hinges 531 that allow the door 530 to be opened to expose the interior of the vehicle storage device 500. A clasping mechanism 532 may be attached to the door 530 to secure the door 530 in a fixed position when closed. Also, the clasping mechanism 532 may include any locking mechanism (not shown) known in the art to limit access to the storage space within the vehicle storage device. Furthermore, an optional top lid 528 may replace the top cover. Alternatively, the material 520 may enclose the top portion of the vehicle storage device 500, forming a box or other structural shape. As with the door 530, the top lid 528 may include a clasping mechanism 529 and a locking mechanism to secure the top lid 528 and prevent exposure to the elements or curious eyes.

[0041] In an alternate embodiment of the present invention, a mounting plate is not included to mount the vehicle storage device to a vehicle. Instead, hooks 251 and fixed clamps 254 are mounted to the frame 210 of the storage device 200, as illustrated in FIG. 8. Depicted is

a rear view of an alternate embodiment of the vehicle storage device 200. Hooks 251, connected to the frame 210, are used to hang the vehicle storage device 200 on a vehicle ladder. Fixed clamps 254 connected to frame 210 attach the vehicle storage device 200 directly to a vehicle ladder. Alternatively, hooks 251 may be substituted with clamps 254. Although the lack of the hinged mounting plate partially inhibits the use of the vehicle ladder, such a vehicle storage device 200 may be desirable in some instances.

[0042] In yet another embodiment of the present invention, the vehicle storage device 100 is not mounted to a vehicle ladder. Instead, the storage device 100 is mounted to a vehicle equalizer hitch or towing hitch. For example, an L-shaped mounting support, as known in the art, may be fixed to either the frame 110 or a mounting plate 150 connected to the frame 110 of the vehicle storage device 100. One end of the mounting support may be secured within an equalizer hitch of a vehicle, thereby supporting the storage device on the back of the vehicle. If the mounting support is attached to a mounting plate 150 of the vehicle storage device 100, the vehicle storage device 100 may be swung on a hinge 152 to allow access to the back of the vehicle to which the vehicle storage device 100 is mounted.

[0043] Other known mounting methods and devices may also be used to attach a storage device 100 to a vehicle. For example, a tire-mounting bracket allows the storage device 100 to be mounted on a spare tire on the back of a vehicle or to the spare tire mounting bracket. Similarly, a storage device 100 may be mounted to a bumper using a bumper-mounting bracket.

[0044] In still another embodiment of the present invention, a recreational equipment carrier, such as a bicycle mount 670, is attached to the vehicle storage device 100 of the present invention. As shown in FIG. 6, the bicycle mount 670 extends over the top of the vehicle storage device 100 to support one or more bicycles. Bicycle support brackets 672 support bicycles set on the bicycle mount 670. Different types of bicycle support brackets 672 may be used as known in the art. Furthermore, the number of bicycle support brackets 672 incorporated with the vehicle storage device 100 is limited only by the size of the bicycle mount 670. The bicycle mount 670 may be fixed to the mounting plate of the vehicle storage device 100 or to another mounting bracket depending upon the type of mounting device used to secure the particular vehicle storage device 100 to the vehicle. Also, a portion of the bicycle mount 670 may controllably rotate about a pivot point 675 thereby allowing a person to rotate any bicycles mounted to the bicycle mount 670 to the side of the vehicle storage device 100 so the contents of

the vehicle storage device 100 may be accessed. Alternatively, the bicycle mount 670 is also removable from the mounting bracket or mounting plate so that it may be stored when not being used to carry bicycles.

[0045] The vehicle storage devices 100 of the present invention may also include locking device attachments capable of accepting a wire lock or bicycle lock. Using the locking device attachments, such as a grommet hole in the material of the vehicle storage device or a lock attachment device 680 (illustrated in FIG. 6), a chain or bicycle lock may be used to lock the vehicle storage device 100 to the vehicle, or bicycles to the vehicle storage device 100.

[0046] Another type of recreation equipment carrier, a ski/snowboard mount 770 for holding skis and/or snowboards, may also be attached to vehicle storage device 100. FIG. 7 illustrates one embodiment of a ski/snowboard mount 770 attached to vehicle storage device 100. The ski/snowboard mount 770 extends over the top of vehicle storage device 100. Support brackets 772 fixed to the ski/snowboard mount 770 provide support for skis or snowboards. Such support brackets 772 are well known in the art, and may be incorporated with the vehicle storage device 100 of the present invention. Like the bicycle mount, the ski/snowboard mount 770 may also be controllably rotated or moved about a pivot point 775 to allow a person to move skis or snowboards attached to the ski/snowboard mount to the side for access to the vehicle storage device 100. In addition, the ski/snowboard mount 770 may include a support base 774 extending below the vehicle storage device 100 to further support the tails of skis or snowboards supported by the ski/snowboard mount 770.

[0047] Alternatively, a side ski/snowboard mount 780 may be incorporated with the vehicle storage device 100 of the present invention. The side ski/snowboard mount 780 may include a rectangular box 782 having a door 784 secured by latch 785. Skis or snowboards may be stored within the rectangular box 782 in order to protect the skis or snowboards from the elements.

[0048] Other known recreational equipment carriers may also be incorporated with the vehicle storage device 100 of the present invention.

[0049] Having thus described certain preferred embodiments of the present invention, it is to be understood that the invention defined by the appended claims is not to be limited by

particular details set forth in the above description, as many apparent variations thereof are possible without departing from the spirit or scope thereof as hereinafter claimed.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239